

AF3 Universal Framing Anchor Type 3 125mm

Catnic Universal Framing Anchor, designed to be used on general timber frame construction, including connecting roof timbers, joist trimmings, and studding. The slotted design allows bending on-site for versatile configuration.



Options

Product Code	Leg Length (mm)	Strap Width (mm)	Gauge/Thickness (mm)	Size (mm x mm)	Weight Per Box (kg)	Weight Per Item (kg)
AF3	125	N/A	1.2	42 X 42	6	0.03

Information

Manufactured from galvanised steel to BS EN10346.

Catnic Universal Framing Anchor are designed to allow nail fixing into timber joist with Type A 3.75mm x 30mm sheradised square twist nails for manual fixing or Type B 3.75 x 35mm sheradised square twist nails for nail gun fixing.

Note: Manufactured from galvanised steel to BS EN10346.

Catnic

Pontypandy Industrial Estate Caerphilly CF83 3GL United Kingdom
 +44 (0)29 2033 7900 | catnic.technical@tatasteeleurope.com
catnic.com

Care has been taken to ensure that the contents of this publication are accurate, but Tata Steel Europe Limited and its subsidiaries, which includes Tata Steel UK Limited, do not accept responsibility or liability for errors or information that is found to be misleading. Before using products or services supplied or manufactured by Tata Steel Europe Limited and its subsidiaries, customers should satisfy themselves as to their suitability.

© Copyright 2024 Tata Steel UK Limited