

CTC47 Truss Clip 47mm

Catnic Truss Clip, a lightweight clip providing a quick and effective method fixing trussed rafters to wall plates in low loading applications as recommended in BS 5268:Part 3. Can also be used as a multipurpose connector providing restraint whenever two timber members cross.



| SWL (kN) | Joist Width (mm) | Leg Length (mm) | Gauge/Thickness (mm) | Weight Per Box (kg) | Weight Per Item (kg) |
|----------|----------------------|-----------------|---|---------------------|----------------------|
| , | , | 88(7 | 8 | | |
| 3.75 | 47 | 100 | 0.9 | 7.5 | 0.075 |
| | SWL (kN) 3.75 | . , | . , , , , , , , , , , , , , , , , , , , | | |

Information

 $\label{thm:manufactured} \textit{Manufactured from galvanised steel to BS EN10346}.$

Catnic Truss Clip is typically installed on the inside wall plate, and should always be fitted vertically to a wall plate, never lying flat or horizontally using 3.75mm x 30mm sheradised square twist nails.

Note: Manufactured from galvanised steel to BS EN10346.

Catnic

Pontypandy Industrial Estate Caerphilly CF83 3GL United Kingdom +44 (0)29 2033 7900 | catnic.technical@tatasteeleurope.com catnic.com

Care has been taken to ensure that the contents of this publication are accurate, but Tata Steel Europe Limited and its subsidiaries, which includes Tata Steel UK Limited, do not accept responsibility or liability for errors or information that is found to be misleading. Before using products or services supplied or manufactured by Tata Steel Europe Limited and its subsidiaries, customers should satisfy themselves as to their suitability.

© Copyright 2024 Tata Steel UK Limited