

SV1000/T Vertical Restraint Strap Twist 100mm

Catnic Light Duty Vertical Restraint Strap, designed for tying vertical loads such as wall plates onto masonry, helping to prevent wind uplift whilst distributing loads



Options

Product Code	Tensile Strength (N)	Strap Width (mm)	Gauge/Thickness (mm)	Size (mm x mm)	Total Strap Length (mm)	Weight Per Box (kg)	Weight Per Item (kg)
SV1000/T100	4000	27	2.3	900 + 100	1000	10	0.5

Information

Manufactured from galvanised steel to BS EN10346.

Light duty vertical restraint straps should be fixed using 75mm x 4.0mm diameter galvanised nails into timber or 50mm long no.12 woodscrews (with wall plugs in masonry for vertical restraint).

Note: Manufactured from galvanised steel to BS EN10346.

Catnic

Pontypandy Industrial Estate Caerphilly CF83 3GL United Kingdom
 +44 (0)29 2033 7900 | catnic.technical@tatasteeleurope.com
catnic.com

Care has been taken to ensure that the contents of this publication are accurate, but Tata Steel Europe Limited and its subsidiaries, which includes Tata Steel UK Limited, do not accept responsibility or liability for errors or information that is found to be misleading. Before using products or services supplied or manufactured by Tata Steel Europe Limited and its subsidiaries, customers should satisfy themselves as to their suitability.

© Copyright 2024 Tata Steel UK Limited