


# Extreme Load Steel Lintel CBP100/100




<b>Wall Construction</b>	CAVITY WALL
<b>Inner Leaf</b>	100
<b>Outer Leaf</b>	100-102
<b>Cavity</b>	100-105
<b>Loading Details</b>	EXTREME LOAD

## Specification

Product Code	Standard Length (mm)	SWL (kN) 1:1/3:1	Weight (kg)	Nominal Height (mm)
CBP100/1002100	2100	88	81.02	263
CBP100/1002200	2200	88	84.88	263
CBP100/1002350	2350	88	90.66	263
CBP100/1002650	2650	88	102.24	263
CBP100/1002700	2700	88	104.17	263
CBP100/1002750	2750	88	106.09	263
CBP100/1002800	2800	88	108.02	263
CBP100/1002850	2850	88	109.95	263
CBP100/1002900	2900	88	111.88	263
CBP100/1003000	3000	88	115.74	263
CBP100/1003050	3050	79	117.67	263
CBP100/1003150	3150	79	121.53	263
CBP100/1003200	3200	79	123.46	263
CBP100/1003300	3300	79	127.32	263
CBP100/1003350	3350	79	129.24	263
CBP100/1003400	3400	79	131.72	263
CBP100/1003450	3450	79	133.10	263
CBP100/1003500	3500	79	135.03	263
CBP100/1003550	3550	79	136.96	263
CBP100/1003600	3600	79	138.89	263
CBP100/1003700	3700	79	142.75	263
CBP100/1003800	3800	79	146.60	263
CBP100/1003900	3900	79	150.46	263
CBP100/1004000	4000	79	154.32	263
CBP100/1004050	4050	79	156.25	263
CBP100/1004100	4100	79	158.18	263
CBP100/1004150	4150	79	160.11	263
CBP100/1004200	4200	79	162.04	263
CBP100/1004250	4250	79	163.97	263
CBP100/1004350	4350	79	167.82	263
CBP100/1004400	4400	79	169.75	263
CBP100/1004500	4500	79	173.61	263
CBP100/1004600	4600	79	177.47	263

Product Code	Standard Length (mm)	SWL (kN) 1:1/3:1	Weight (kg)	Nominal Height (mm)
CBP100/1004650	4650	79	179.40	263
CBP100/1004800	4800	79	185.18	263
CBP100/1004900	4900	74	189.04	263
CBP100/1004950	4950	74	190.67	263
CBP100/1005050	5050	74	194.82	263
CBP100/1005200	5200	70	200.62	263
CBP100/1005250	5250	70	202.55	263
CBP100/1005400	5400	70	208.33	263
CBP100/1005600	5600	66	216.04	263
CBP100/1005700	5700	66	219.90	263



All ratios are shown inner to outer

- The SWL (safe working load) is based on the total UDL (uniform distributed load) over maximum span using 150mm end bearings.
- Standard lengths are available in increments of 50mm at lengths up to 6600mm.

**Note:** Whilst the above information is intended to offer general guidance regarding typical applications, it should not be considered as comprehensive. Requirements not fully covered by the above should be referred to our technical services department for individual consideration.

## Catnic

Pontypany Industrial Estate Caerphilly CF83 3GL United Kingdom  
+44 (0)29 2033 7900 | [catnic.technical@tatasteeleurope.com](mailto:catnic.technical@tatasteeleurope.com)

[www.catnic.com](http://www.catnic.com)

Care has been taken to ensure that the contents of this publication are accurate, but Tata Steel Europe Limited and its subsidiaries, which includes Tata Steel UK Limited, do not accept responsibility or liability for errors or information that is found to be misleading. Before using products or services supplied or manufactured by Tata Steel Europe Limited and its subsidiaries, customers should satisfy themselves as to their suitability.

© Copyright 2024 Tata Steel UK Limited.