

## **PVC-u Soffit Cladding** FCGREY

 Wall Construction
 N/A

 Inner Leaf
 N/A

 Outer Leaf
 N/A

 Cavity
 N/A

 Loading Conditions
 N/A DUTY



## Specification

| Product Code | Standard Length (mm) | SWL (kN) | Weight (kg) | Nominal Height (mm) |
|--------------|----------------------|----------|-------------|---------------------|
| FCGREY0750   | 750                  | N/A      | 0.21        | N/A                 |
| FCGREY0900   | 900                  | N/A      | 0.25        | N/A                 |
| FCGREY1050   | 1050                 | N/A      | 0.29        | N/A                 |
| FCGREY1200   | 1200                 | N/A      | 0.33        | N/A                 |
| FCGREY1350   | 1350                 | N/A      | 0.37        | N/A                 |
| FCGREY1500   | 1500                 | N/A      | 0.41        | N/A                 |
| FCGREY1650   | 1650                 | N/A      | 0.46        | N/A                 |
| FCGREY1800   | 1800                 | N/A      | 0.50        | N/A                 |
| FCGREY1950   | 1950                 | N/A      | 0.54        | N/A                 |
| FCGREY2100   | 2100                 | N/A      | 0.58        | N/A                 |
| FCGREY2250   | 2250                 | N/A      | 0.63        | N/A                 |
| FCGREY2400   | 2400                 | N/A      | 0.66        | N/A                 |
| FCGREY2550   | 2550                 | N/A      | 0.71        | N/A                 |
| FCGREY2700   | 2700                 | N/A      | 0.74        | N/A                 |
| FCGREY2850   | 2850                 | N/A      | 0.79        | N/A                 |
| FCGREY3000   | 3000                 | N/A      | 0.82        | N/A                 |
| FCGREY3300   | 3300                 | N/A      | 0.91        | N/A                 |
| FCGREY3600   | 3600                 | N/A      | 0.99        | N/A                 |
| FCGREY3900   | 3900                 | N/A      | 1.07        | N/A                 |
| FCGREY4200   | 4200                 | N/A      | 1.16        | N/A                 |
| FCGREY4575   | 4575                 | N/A      | 1.26        | N/A                 |
| FCGREY4800   | 4800                 | N/A      | 1.33        | N/A                 |
| FCGREY5100   | 5100                 | N/A      | 1.41        | N/A                 |

 All external wall lintels fitted with lintel cladding must be installed with a flexible damp proof course (DPC) ensuring that the DPC projects beyond the front face of the cladding.

**Note:** Whilst the above information is intended to offer general guidance regarding typical applications, it should not be considered as comprehensive. Requirements not fully covered by the above should be referred to our technical services department for individual consideration.

## Catnic

Pontypandy Industrial Estate Caerphilly CF83 3GL United Kingdom +44 (0)29 2033 7900

catnic.technical@tatasteeleurope.com catnic.com

## Tata Steel UK Limited

18 Grosvenor Place, London, SW1X 7HS Registered in England No. 02280000 Care has been taken to ensure that the contents of this publication are accurate, but Tata Steel Europe Limited and its subsidiaries, which includes Tata Steel UK Limited, do not accept responsibility or liability for errors or information that is found to be misleading. Before using products or services supplied or manufactured by Tata Steel Europe Limited and its subsidiaries, customers should satisfy themselves as to their suitability.

© Copyright 2025 Tata Steel UK Limited