

# PVC-u Soffit Cladding

## FCWHITE

Lintel Soffitt Cladding is an optional cladding that provides extra protection, especially in coastal regions and in situations where much of the lintel soffit is exposed.

<b>Wall Construction</b>	N/A
<b>Inner Leaf</b>	N/A
<b>Outer Leaf</b>	N/A
<b>Cavity</b>	N/A
<b>Loading Conditions</b>	N/A DUTY



## Specification

Product Code	Standard Length (mm)	SWL (kN)	Weight (kg)	Nominal Height (mm)
FCWHITE0750	750	N/A	0.21	N/A
FCWHITE0900	900	N/A	0.25	N/A
FCWHITE1050	1050	N/A	0.29	N/A
FCWHITE1200	1200	N/A	0.33	N/A
FCWHITE1350	1350	N/A	0.37	N/A
FCWHITE1500	1500	N/A	0.41	N/A
FCWHITE1650	1650	N/A	0.46	N/A
FCWHITE1800	1800	N/A	0.50	N/A
FCWHITE1950	1950	N/A	0.54	N/A
FCWHITE2100	2100	N/A	0.58	N/A
FCWHITE2250	2250	N/A	0.62	N/A
FCWHITE2400	2400	N/A	0.66	N/A
FCWHITE2550	2550	N/A	0.70	N/A
FCWHITE2700	2700	N/A	0.75	N/A
FCWHITE2850	2850	N/A	0.79	N/A
FCWHITE3000	3000	N/A	0.83	N/A
FCWHITE3300	3300	N/A	0.91	N/A
FCWHITE3600	3600	N/A	0.99	N/A
FCWHITE3900	3900	N/A	1.08	N/A
FCWHITE4200	4200	N/A	1.17	N/A
FCWHITE4575	4575	N/A	1.26	N/A
FCWHITE4800	4800	N/A	1.33	N/A
FCWHITE5100	5100	N/A	1.40	N/A

- All external wall lintels fitted with lintel cladding must be installed with a flexible damp proof course (DPC) ensuring that the DPC projects beyond the front face of the cladding.

## Benefits

- Lintel Soffitt Cladding is an optional cladding that provides extra protection, especially in coastal regions and in situations where much of the lintel soffit is exposed.
- Suitable for use with Cougar lintels (CG, CH, CX) timber frame lintels (CTF5, CTF7, CTF9, CN23), thermally broken lintels (TS, TH, TX) and External solid wall lintels (CN71 and CN81).

**Note:** Whilst the above information is intended to offer general guidance regarding typical applications, it should not be considered as comprehensive. Requirements not fully covered by the above should be referred to our technical services department for individual consideration.

### Catnic

Pontypandy Industrial Estate Caerphilly CF83 3GL  
United Kingdom  
+44 (0)29 2033 7900

[catnic.technical@tatasteeleurope.com](mailto:catnic.technical@tatasteeleurope.com)

[catnic.com](http://catnic.com)

### Tata Steel UK Limited

18 Grosvenor Place, London, SW1X 7HS  
Registered in England No. 02280000

Care has been taken to ensure that the contents of this publication are accurate, but Tata Steel Europe Limited and its subsidiaries, which includes Tata Steel UK Limited, do not accept responsibility or liability for errors or information that is found to be misleading. Before using products or services supplied or manufactured by Tata Steel Europe Limited and its subsidiaries, customers should satisfy themselves as to their suitability.

© Copyright 2026 Tata Steel UK Limited