

Galvanised Steel Plaster Key PKS

Wall Construction	N/A
Inner Leaf	N/A
Outer Leaf	N/A
Cavity	N/A
Loading Details	N/A

Specification

Product Code	Standard Length (mm)	SWL (kN)	Weight (kg)	Nominal Height (mm)
PKS87	1200	N/A	3.70	N/A

- External plaster key simply clips into place and is secured using a full length of adhesive bead. The PKS87 Plaster Key MUST be fitted to the lintel before the lintel is installed.
- Unless required for immediate use on site, the product should be stored in a clean dry environment

Note: Whilst the above information is intended to offer general guidance regarding typical applications, it should not be considered as comprehensive. Requirements not fully covered by the above should be referred to our technical services department for individual consideration.

Catnic

Pontypandy Industrial Estate Caerphilly CF83 3GL United Kingdom
+44 (0)29 2033 7900 | catnic.technical@tatasteeleurope.com

www.catnic.com

Care has been taken to ensure that the contents of this publication are accurate, but Tata Steel Europe Limited and its subsidiaries, which includes Tata Steel UK Limited, do not accept responsibility or liability for errors or information that is found to be misleading. Before using products or services supplied or manufactured by Tata Steel Europe Limited and its subsidiaries, customers should satisfy themselves as to their suitability.

© Copyright 2024 Tata Steel UK Limited.